



All dimensions are in mm.

Sensor \ Motor	PMSM	BLDC	DC BRUSH	STEP (2-ph)	STEP <sup>3</sup> (3-ph)
Incr. Encoder	T		T	T	T
Incr. Encoder + Hall	T	T			
Analog Sin/Cos encoder	T	T	T	T	T
SSI <sup>1</sup>	T		T	T	T
BiSS-C <sup>1</sup>	T		T	T	T
EnDAT <sup>1,2</sup>	T		T	T	T
Linear Halls	T				
Tacho			T		
Open-loop (no sensor)				T	T

<sup>1</sup> Only with external circuit

<sup>2</sup> Available starting with F514K firmware version

<sup>3</sup> Sensors are used only for step loss detection

Mating connectors							
Connector	Description						
J1	Socket 2x25 pins, 1.27x1.27mm pitch, square 0.4 mm pins						
	If J3&J4 are soldered on motherboard		If J3&J4 are used with mating SSQ connectors				
	Harwin	M50-3152542	Harwin	M50-3002545			
J2	Socket 2x20 pins, 1.27x1.27mm pitch, square 0.4 mm pins						
	If J3&J4 are soldered on motherboard		If J3&J4 are used with mating SSQ connectors				
	Harwin	M50-3152042	Harwin	M50-3002045			
J3	To use full current capabilities of the drive, solder these pins directly to the motherboard without using socket connectors						
	High-current socket 2 pins, 2.54 mm pitch, square 0.635 mm pins				SSQ-108-01-G-S		
	-use only if nominal current is < 8A-						
J4	To use full current capabilities of the drive, solder these pins directly to the motherboard without using socket connectors						
	High-current socket 2 pins, 2.54 mm pitch, square 0.635 mm pins				SSQ-102-01-G-S		
	-use only if nominal current is < 8A-						
J5+J7	To use full current capabilities of the drive, solder these pins directly to the motherboard without using socket connectors						
	High-current socket 2x2 pins, 2.54 mm pitch, square 0.635 mm pins				SSQ-102-01-G-D		
-use only if nominal current is < 8A-							

- 4 digital inputs, 12-36V, PNP/NPN programmable: 2 for limit switches, 2 general-purpose
- 4 digital outputs, 5-36V, 0.5A, NPN open-collector: Ready, Error, 2 general-purpose
- 2 analogue inputs: 12-bit, 0-5V: Reference, Feedback or general purpose
- RS-232 serial & dual RJ45 CAN connectors
- TMLCAN and CANopen (CiA 301 v4.2, CiA 305 v.2.2.13 and CiA 402 v3.0) protocols selectable by h/w axis ID pin inputs
- 127 h/w addresses in CANopen mode and 196 h/w addresses in TMLCAN mode
- 16k x 16 SRAM memory for data acquisition
- 16k x16 E<sup>2</sup>ROM to store setup data, TML motion programs, cam tables and other user data
- NTC/PTC analogue Motor Temperature sensor input
- Operating ambient temperature: 0-40°C (over 40°C with derating)
- Programmable protections: short-circuit between motor phases or motor phases to GND, over/under-voltage, over-current, I<sup>2</sup>t, control error

\* with external heat sink

Name EP	First edition January 17, 2019	Document template: P099.TQT.564.0001	Last edition September 2, 2022	Visa : GC
 TECHNOSOFT	Title of document	iMOTIONCUBE-CAN PRODUCT DATA SHEET	N° document <b>P025.126.E101.DSH.10J</b>	Page: 1 of 5

## Connector Description

Pin	Name	Type	Description
1..28	Reserved	-	Reserved
29	CAN-Hi	I/O	CAN-Bus positive line (dominant high)
30	Reserved	-	Reserved
31	CAN-Lo	I/O	CAN-Bus negative line (dominant low)
J2	32	Reserved	- Reserved
	33	+5V	O +5V output power supply
	34	GND	- Ground
	35..39	Reserved	- Reserved
	40	GND	- Ground
Pin	Name	Type	Description
1,2	A/A+	O	Phase A for 3-ph motors, A+ for 2-ph steppers, Motor+ for DC brush motors
J3	3,4	B / A-	O Phase B for 3-ph motors, A- for 2-ph steppers, Motor- for DC brush motors
	5,6	C / B+	O Phase C for 3-ph motors, B+ for 2-ph steppers
	7,8	CR / B-	O Chopping resistor / Phase B- for step motors
Pin	Name	Type	Description
1	232RX	I	RS232 data reception
2	Enc1 A+/Sin1+	I	Incr. encoder # A+ diff. input, analogue encoder #1 Sin+ diff. input.
3	232TX	O	RS232 data transmission
4	Enc1 A-/Sin1-	I	Incr. encoder #1 A- diff. input, analogue encoder #1 Sin1- diff. input
5	AxisID 0	I	Axis ID / Address input #0. Analogue input, 0-5V
6	Enc1 B+/Cos1+	I	Incr. encoder # B- diff. input, analogue encoder #1 Cos+ diff. input.
7	AxisID 1	I	Axis ID / Address input #1. Analogue input, 0-5V
8	ENC1B-/Cos1-	I	Incr. encoder #1 B- diff. input, analogue encoder Cos1- diff. input
9	AxisID 2	I	Axis ID / Address input #2. Analogue input, 0-5V
10	Enc1 Z+	I	Incr. encoder #1 Z+ diff. input.
11	CAN-Hi	-	CAN-Bus positive line (dominant high)
12	Enc1 Z-	I	Incr. encoder Z- diff. input
13	CAN-Lo	-	CAN-Bus negative line (dominant low)
14	Hall1	I/O	Hall 1 sensor
J5	15	ENA1	I Enable circuit input1; connect ENA1&ENA2 to +24V to activate motor operation
	16	Hall2	I/O Hall 2 sensor
	17	ENA2	I Enable circuit input2; connect ENA1&ENA2 to +24V to activate motor operation
	18	Hall3	I Hall 3 sensor
	19	Ref	I Analogue input, 12-bit, 0-5V. Used to read an analog position, speed or torque reference, or as general purpose analogue input
	20	Fdbk	I Analogue input, 12-bit, 0-5V. Used to read an analogue position or speed feedback, or as general purpose analogue input
	21	+Vlog	I Positive terminal for logic supply 9-36V <sub>DC</sub>
	22	+5V <sub>OUT</sub>	O 5V output supply. Max 300mA for feedback sensors and I/Os
	23	IN0	I 12-36V, digital input #0, programmable NPN or PNP, general-purpose
	24	OUT0	O 24 digital output #0, NPN, general-purpose
	25	IN1	I 12-36V, digital input #1, programmable NPN or PNP, general-purpose

<sup>1</sup> Operating temperature can be extended up to +65°C with reduced current and power ratings.<sup>2</sup> iMOTIONCUBE can be operated in vacuum (no altitude restriction), but at altitudes over 2,500m, current and power rating are reduced due to thermal dissipation efficiency.

26	OUT1	O	24V digital output #1, NPN, general-purpose
27	IN2/LSP	I	12-36V, digital input #2, programmable NPN or PNP, positive limit switch
28	Out2/ Error	O	24V digital output #2, NPN, drive error
29	In3/LSN	I	12-36V, digital input #3, programmable NPN or PNP type, negative limit switch
30	Out3/ Ready	O	24V digital output 3, NPN type, drive ready
31	TMOT	I	Motor temperature sensor input. Analogue input, 0-3.3V
32..34	Reserved	-	Reserved
35	GND	-	Ground
36	GND	-	Ground
37-40	Reserved	-	Reserved
41	Enc2 A	I	Incr. encoder #2 A digital input, 0-3.3V
42	SIN2	I	Analogue encoder #2 SIN input, 0-3.3V
43	Enc2 B	I	Incr. encoder #2 B digital input, 0-3.3V
44	COS2	I	Analogue encoder #2 COS input, 0-3.3V
45	Enc2 Z	I	Incr. encoder #2 Z digital input, 0-3.3V
46	+5Vout	O	5V output supply. Max 300mA for feedback sensors and I/Os
47..50	Reserved	-	Reserved

## Pin Name Type Description

J4	1,2	+V <sub>MOT</sub>	I	Positive terminal of the motor supply
----	-----	-------------------	---	---------------------------------------

## Pin Name Type Description

J5	1,2	GND	-	Negative return (ground) of the motor supply
----	-----	-----	---	---

## Pin Name Type Description

J7	1	Earth	-	Earth connection
----	---	-------	---	------------------

## Electrical characteristics

All parameters measured under the following conditions (unless otherwise specified):

- Tamb = 0...40°C, VLOG = 24 VDC; VMOT = 80VDC
- Supplies start-up / shutdown sequence: -any-
- Load current (sinusoidal amplitude / continuous BLDC, DC, stepper) = 20A

Operating Conditions		Min	Typ	Max	Units
Ambient temperature <sup>1</sup>		0		+40	°C
Ambient humidity	Non-condensing	0		90	%R <sub>h</sub>
Altitude / pressure <sup>2</sup>	Altitude (vs. sea level) Ambient Pressure	-0.1 0 <sup>2</sup>	0 ÷ 2 0.75 ÷ 1	2 10.0	Km atm
Storage Conditions		Min	Typ	Max	Units
Ambient temperature		-40		+85	°C
Ambient humidity	Non-condensing	0		100	%R <sub>h</sub>
Ambient Pressure		0		10.0	atm
Mechanical Mounting		Min	Typ	Max	Units
Airflow		natural convection <sup>3</sup> , closed box			

<sup>3</sup> It is recommended to mount the iMOTIONCUBE on a metallic support using the provided mounting holes, for better reliability and reduced de-rating due to heat dissipation

Name EP	First edition January 17, 2019	Document template: P099.TQT.564.0001	Last edition September 2, 2022	Visa : GC
 TECHNOSOFT	Title of document	iMOTIONCUBE-CAN PRODUCT DATA SHEET	Nº document <b>P025.126.E101.DSH.10J</b>	Page: 2 of 5

Environmental Characteristics		Min	Typ	Max	Units
Size (Length x Width x Height)		60 x 40 x 28.2 ~2.36 x 1.58 x 1.11		mm inch	
Weight		Without mating connectors		45	g
Power dissipation		Idle (no load)		3.6	W
Operating		Operating		11	%
Efficiency				98	
Cleaning agents		Dry cleaning is recommended		Only Water- or Alcohol-based	
Protection degree		According to IEC60529, UL508		IP20	-
Logic Supply Input (+V <sub>LOG</sub> )		Min	Typ	Max	Units
Supply voltage	Nominal values	9		36	V <sub>DC</sub>
	Absolute maximum values, drive operating but outside guaranteed parameters	8		40	V <sub>DC</sub>
	Absolute maximum values, surge (duration ≤ 10ms) <sup>†</sup>	-1		+45	V
Supply current	No Load on Digital Outputs	+V <sub>LOG</sub> = 9V	300		mA
		+V <sub>LOG</sub> = 12V	250		
		+V <sub>LOG</sub> = 24V	150		
		+V <sub>LOG</sub> = 36V	100		
Motor Supply Input (+V <sub>MOT</sub> )		Min	Typ	Max	Units
Supply voltage	Nominal values	12	80	90	V <sub>DC</sub>
	Absolute maximum values, drive operating but outside guaranteed parameters	11		94	V <sub>DC</sub>
	Absolute maximum values, surge (duration ≤ 10ms) <sup>†</sup>	-1		95	V
Supply current	Idle		1	5	mA
	Operating	-40	±20	+40	A
	Absolute maximum value, short-circuit condition <sup>†</sup> (duration ≤ 10ms)			45	A
Motor Outputs (A/A+, B/A-, C/B+, CR/B-)		Min	Typ	Max	Units
Nominal output current, continuous	for DC brushed, steppers and BLDC motors with Hall-based trapezoidal control			20	A
	for PMSM motors with FOC sinusoidal control (sinusoidal amplitude value)			20	
	for PMSM motors with FOC sinusoidal control (sinusoidal effective value)			14.2	
Motor output current, peak	maximum 10s	-40		+40	A
Short-circuit protection threshold	measurement range			±45	A
Short-circuit protection delay		5	10		μs
On-state voltage drop	Nominal output current; including typical mating connector contact resistance		±0.3	±0.5	V
Off-state leakage current			±0.5	±1	mA
Motor inductance (phase-to-phase)	Recommended value, for current ripple Max ±5% of full range; +V <sub>MOT</sub> = 80 V	F <sub>PWM</sub>			μH
		20 kHz	330		
		40 kHz	150		
		60 kHz	120		
		80 kHz	80		
		100 kHz	60		
	Minimum value, limited by short-circuit protection; +V <sub>MOT</sub> = 80 V	20 kHz	120		μH
		40 kHz	40		
		60 kHz	30		
		80 kHz	15		
Motor electrical time-constant (L/R)	Recommended value for ±5% current measurement error	100 kHz	8		μs
		20 kHz	250		
		40 kHz	125		
		60 kHz	100		
		80 kHz	63		
Current measurement	FS = Full Scale accuracy	100 kHz	50		%FS

Digital Hall Inputs (Hall1, Hall2, Hall3)		Min	Typ	Max	Units
Mode compliance		TTL / CMOS / Open-collector			
Default state		Input floating (wiring disconnected)		Logic HIGH	
Input voltage	Logic "LOW"		0	0.8	V
	Logic "HIGH"	1.8			
	Floating voltage (not connected)		4.5		
	Absolute maximum, surge (duration ≤ 1s) <sup>†</sup>	-10		+15	
Input current	Logic "LOW"; Pull to GND		5	3	mA
	Logic "HIGH"; Internal 1KΩ pull-up to +5	0	0	0	
Minimum pulse width		2			μs
ESD protection	Human body model	±5			kV
Linear Hall Inputs (LH1, LH2, LH3)		Min	Typ	Max	Units
Input voltage	Operational range	0	0.5÷4.5	4.9	V
	Absolute maximum values, continuous	-7		+7	
	Absolute maximum, surge (duration ≤ 1s) <sup>†</sup>	-11		+14	
Input current	Input voltage 0...+5V	-1	±0.9	+1	mA
Interpolation Resolution	Depending on software settings			10	bits
Frequency		0		1	kHz
ESD protection	Human body model	±1			kV
Encoder #1 Inputs (A2+, A2-, B2+, B2-, Z2+, Z2-)¹		Min	Typ	Max	Units
Single-ended mode compliance	Leave negative inputs disconnected	TTL / CMOS / Open-collector			
	Logic "LOW"			1.6	V
Input voltage, single-ended mode A/A+, B/B+	Logic "HIGH"	1.8			
	Floating voltage (not connected)		4.7		
Input voltage, single-ended mode Z/Z+	Logic "LOW"			1.2	V
	Logic "HIGH"	1.4			
	Floating voltage (not connected)		4.7		
Input current, single-ended mode A/A+, B/B+, Z/Z+	Logic "LOW"; Pull to GND		2.5	3	mA
	Logic "HIGH"; Internal 2.2KΩ pull-up to +5	0	0	0	
Differential mode compliance	For full RS422 compliance, see <sup>2</sup>	TIA/EIA-422-A			
Input voltage, differential mode	Hysteresis	±0.06	±0.1	±0.2	V
	Common-mode range (A+ to GND, etc.)	-7		+7	
Input impedance	A1+, B1+, Z1+ to GND		2.2		kΩ
	A1-, B1-, Z1- to GND		3.6		
Input frequency	Single-ended mode	0		500	kHz
	Differential mode	0		10	MHz
Input voltage, any pin to GND	Absolute maximum, surge duration ≤ 1s <sup>†</sup>	-11		+14	V
	ESD protection	human body model	±1		
Encoder #2 Inputs (A2, B2, Z2)		Min	Typ	Max	Units
Single ended mode compliance	TTL / CMOS / Open collector				V
	Logic "LOW"			0.8	
Input voltage, single-ended mode	Logic "HIGH"	2			mA
	Logic "LOW"			0.1	
Input current, single-ended mode	Logic "HIGH"			0.1	

<sup>1</sup> Encoder #1 differential input pins do not have internal 120Ω termination resistors connected across. <sup>2</sup> For full RS-422 compliance, 120Ω termination resistors must be connected across the differential pairs

Name EP	First edition January 17, 2019	Document template: P099.TQT.564.0001	Last edition September 2, 2022	Visa : GC
 TECHNOSOFT	Title of document <b>iMOTIONCUBE-CAN</b> <b>PRODUCT DATA SHEET</b>	Nº document <b>P025.126.E101.DSH.10J</b>		Page: 3 of 5

Sin-Cos Encoder Inputs (Sin+, Sin-, Cos+, Cos-)¹		Min	Typ	Max	Units	
Input voltage, differential	Sin+ to Sin-, Cos+ to Cos-	0.8	1	1.25	V <sub>PP</sub>	
Input voltage, any pin to GND	Operational range	-1	2.5	4	V	
	Absolute maximum values, continuous	-7		+7		
	Absolute maximum, surge (duration ≤ 1s)⁴	-11		+14		
	Absolute maximum, continuous					
Input impedance	Differential, Sin+ to Sin-, Cos+ to Cos-		120		Ω	
Resolution with interpolation	Common-mode, to GND		2.2		kΩ	
Frequency	Software selectable, for one sine/cosine period	2		10	bits	
ESD protection	Sin-Cos interpolation	0		450	kHz	
	Quadrature, no interpolation	0		10	MHz	
	Human body model	±2			kV	
Digital Inputs (IN0, IN1, IN2/LSP, IN3/LSN)¹		Min	Typ	Max	Units	
Mode compliance	PNP					
Default state	Input floating (wiring disconnected)	Logic LOW				
Input voltage	Logic "LOW"	-10	0	2.2	V	
	Logic "HIGH"	6.3		36		
	Floating voltage (not connected)		0			
	Absolute maximum, continuous	-10		+39		
	Absolute maximum, surge (duration ≤ 1s)⁴	-20		+40		
Input current	Logic "LOW"; pulled to GND		0		mA	
	Logic "HIGH"		6	8		
Mode compliance	NPN					
Default state	Input floating (wiring disconnected)	Logic HIGH				
Input voltage	Logic "LOW"	-10		2.2	V	
	Logic "HIGH"	6.3		36		
	Floating voltage (not connected)		V <sub>LOG</sub> -1			
	Absolute maximum, continuous	-10		+36		
	Absolute maximum, surge (duration ≤ 1s)⁴	-20		+40		
Input current	Logic "LOW"; Pulled to GND		6	8	mA	
	Logic "HIGH"; Pulled to +24V		0			
Input frequency		0		150	kHz	
Minimum pulse		3.3			μs	
ESD protection	Human body model	±2			kV	
Digital Outputs (OUT0, OUT1, OUT2/Error, OUT3/Ready)		Min	Typ	Max	Units	
Mode compliance	All outputs (OUT0, OUT1, OUT2/Error, OUT3/Ready)	NPN 24V				
Default state	Not supplied (+V <sub>LOG</sub> floating or to GND)	High-Z (floating)				
	Immediately after power-up	OUT0, OUT1	Logic "HIGH"			
		OUT2/Error, OUT3/Ready	Logic "LOW"			
	Normal operation	OUT0, OUT1, OUT2/Error	Logic "HIGH"			
		OUT3/Ready	Logic "LOW"			
Output voltage	Logic "LOW"; output current = 0.5A			0.8	V	
	Logic "HIGH", external load to +V <sub>LOG</sub>		V <sub>LOG</sub>			
	Absolute maximum, continuous	-0.5		36V		
Output current	Logic "LOW", sink current, continuous			0.5	A	
	Logic "HIGH", leakage current; external load to +V <sub>LOG</sub> ; V <sub>out</sub> = V <sub>LOG</sub> max = 39V			0.2	mA	
Minimum pulse width		2			μs	
ESD protection	Human body model	±15			kV	

¹ The digital inputs are software selectable as PNP or NPN

Name EP	First edition January 17, 2019	Document template: P099.TQT.564.0001	Last edition September 2, 2022	Visa : GC
 TECHNOSOFT	Title of document <b>iMOTIONCUBE-CAN</b> <b>PRODUCT DATA SHEET</b>	Nº document <b>P025.126.E101.DSH.10J</b>		Page: 4 of 5

² For full RS-422 compliance, 120Ω termination resistors must be connected across the differential pairs, as close as possible to the drive input pins.

# iMOTIONCUBE-CAN DATASHEET

P/N: P025.126.E101

Enable circuit (ENA1, ENA2)		Min	Typ	Max	Units
Enable function		Disables motor power when either ENA1 or ENA2 is disconnected from the power source			
Mode compliance		PNP			
Default state		Input floating (wiring disconnected) Logic LOW			
Input voltage	Logic "LOW"	-10		2.2	V
	Logic "HIGH"	6.3		36	
	Absolute maximum, continuous	-10		+39	
Input current	Logic "LOW"; pulled to GND		0		mA
	Logic "HIGH", pulled to +Vlog		9	13	
Pulse duration	Ignored low-high-low			1	ms
	Ignored high-low-high			1.5	
	Accepted pulse	tbd			
ESD protection	Human body model	±2			kV
Analog 0...5V Inputs (REF, FDBK)		Min	Typ	Max	Units
Input voltage	Operational range	0		4.95	V
	Absolute maximum values, continuous	-12		+18	
	Absolute maximum, surge (duration ≤ 1s) <sup>†</sup>			±36	
Input impedance	To GND		8		kΩ
Resolution			12		bits
Integral linearity				±2	bits
Offset error			±2	±10	bits
Gain error			±1%	±3%	% FS <sup>1</sup>
Bandwidth (-3dB)	Software selectable	0		1	KHz
ESD protection	Human body model	±2			kV

RS-232		Min	Typ	Max	Units	
Compliance		TIA/EIA-232-C				
Bit rate		Software selectable		9600	115200 Baud	
Short-circuit		232TX short to GND				
ESD protection		Guaranteed Human body model				
CAN-Bus		Min	Typ	Max	Units	
Compliance		ISO11898, CIA-301v4.2 & 402v3.0				
Bit rate		Software selectable		125	1000 Kbps	
Bus length		1Mbps		25	m	
500Kbps		500Kbps		100		
≤ 250Kbps		≤ 250Kbps		250		
Resistor		Between CAN-Hi, CAN-Lo none on-board				
Node addressing		Strapping option (AxisID0,1,2) 1 ÷ 127 (CANopen); 1-195 & 255 (TMLCAN)				
ESD protection		Human body model ±15				
Supply Output (+5V)		Min	Typ	Max	Units	
Output voltage		Current sourced = 500mA 4.8				
Output current		600		650	mA	
Short-circuit		NOT protected				
Over-voltage		NOT protected				
ESD protection		Human body model ±2				

<sup>†</sup> Stresses beyond values listed under "absolute maximum ratings" may cause permanent damage to the device. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

<sup>1</sup> "FS" stands for "Full Scale"

Name EP	First edition January 17, 2019	Document template: P099.TQT.564.0001	Last edition September 2, 2022	Visa : GC
 TECHNOSOFT	Title of document  <b>iMOTIONCUBE-CAN PRODUCT DATA SHEET</b>	Nº document  <b>P025.126.E101.DSH.10J</b>		Page: 5 of 5