

All dimensions are in mm. Drawing not to scale. Pins facing downward view.

Motor – sensor configurations					
Sensor \ Motor	PMSM	BLDC	DC BRUSH	STEP (2-ph)	STEP (3-ph)
Incr. Encoder	☒		☒	☒	
Incr. Encoder + Dig. Hall	☒	☒			
Linear Halls	☒				
Digital Hall control only	☒				
BISS / SSI / EnDAT / TAMAGAWA / Nikon / Sanyo Denki / Panasonic	☒	☒	☒	☒	
Tacho			☒		
Open-loop (no sensor)				☒	☒

▪ Features

- Motion controller and drive in a single compact unit based on MotionChip™ technology
 - Universal solution for control of rotary and linear brushless, brushed and 2 or 3-phase step motors
 - Advanced motion control features, including CSP, CSV, CST, PVT, S-curve, electronic gearing, camming, and more.
 - Motor supply: 48V nominal
 - Motor output current:
 - Nominal: $4.5A_{RMS}$ / 6.3A amplitude for PMSM motors
5.5A for DC / BLDC / Step motors
 - Peak: $11.3A_{RMS}$ / 16A amplitude
 - Logic supply: 24V nominal, 48V max
 - Feedback#1 and Feedback#2 can be:
 - 1 x Hall sensor interface (digital or linear)
 - Feedback#1 and Feedback#2 can be:
 - Incremental encoder A / B (index Z only for Feedback #1): differential or single-ended;
 - Absolute encoder: differential or single-ended. Supported protocols:SSI, BiSS, EnDAT, Tamagawa, Panasonic, Nikon, Sanyo Denki.
 - 1 x analogue input, 12-bit, software selectable: 0-5V or $\pm 10V$; Reference, Feedback or General purpose
 - 3 x digital inputs: 2 for limit switches + one Enable, NPN, pull-up on-board to +5V. Pull to GND to activate.
 - 3 x configurable I/Os, each software selectable as:
 - Digital input, NPN, with pull-up on-board to +5V. Pull to GND to activate;
 - Digital output, NPN (open-collector), with pull-up on-board to +5V. Sink current: $1 \times 1.5A$ to drive inductive loads (such as mechanical brake), $2 \times 0.1A$.
 - Communication interfaces: RS232; USB; TMLCAN and CANopen (CiA 301 v4.2, CiA 305 v.2.2.13 and CiA 402 v3.0) protocols
 - 24Kwords E²ROM to store setup data, TML motion programs, cam tables and other user data
 - 16Kwords SRAM memory for data acquisition
 - Operating ambient temperature: 0-40°C (over 40°C with de-rating)
 - Programmable protections: any short-circuit between motor phases, GND and/or supply, over/under-voltage, over-current, I²t drive & motor, control error
 - 3 AxisID inputs, for hardware-based address setting
 - >98% voltage efficiency, >98% power efficiency

Name ALN	First edition November 8, 2023	Document template: P099.TQT.564.0001	Last edition March 12, 2025	Visa:
 TECHNOSOFT	Title of document Micro 4804 MZ-CAN PRODUCT DATA SHEET	N° document P020.002.E102.DSH.10G		Page: 1 of 5



Pin	Name	Type	Description
1	+Vlog	I	Positive terminal of the logic supply input: 6 to 48 V _{DC}
2	A/A+	O	Phase A for 3-ph motors, A+ for 2-ph steppers, Motor+ for DC brush motors
3	GND	-	Ground return for logic supply
4	B/A-	O	Phase B for 3-ph motors, A- for 2-ph steppers, Motor- for DC brush motors
5	GND	-	Ground return for motor supply & shield for motor windings cable
6	C/B+	O	Phase C for 3-ph motors, B+ for 2-ph steppers
7	+Vmot	I	Positive terminal of the motor supply: 7 to 48 VDC
8	Cr/B-	O	Chopping resistor / Phase B- for 2-ph steppers
9	BFS	I	Boot Fail-Safe: Connect to GND to reprogram firmware in the improbable case when a power loss occurs during a firmware update and the normal firmware recovery fails
10	ID2	I	AxisID2 selection pin. See AxisID register settings table.
11	... Rsvd.	-	Reserved. Do not connect.
14			
15	GND	-	Ground return and shield
16	GND	-	Ground return and shield
17	... Rsvd.	-	Reserved. Do not connect.
20			
21	ID0	I	AxisID0 selection pin. See AxisID register settings table.
22	ID1	I	AxisID1 selection pin. See AxisID register settings table.
23	232TX	O	RS-232 Data Transmission.
24	232RX	I	RS-232 Data Reception.
25	CAN Hi	O	CAN-Bus positive line (dominant high)
26	CAN Lo	I	CAN-Bus negative line (dominant low)
27	IN2/LSP	I	5-48V digital NPN input. Positive limit switch input
28	IN3/LSN	I	5-48V digital NPN input. Negative limit switch input
29	IN5/Enable	I	5-48V digital NPN input. Drive Enable input
30	I/O0	I/O	5-48V 1.5A NPN (sink) general-purpose digital programmable input IN0 or output OUT0
31	I/O1	I/O	5-48V 0.1A NPN (sink) general-purpose digital programmable input IN1 or output OUT1
32	I/O4	I/O	5-48V 0.1A NPN (sink) general-purpose digital programmable input IN4 or output OUT4
33	GND	-	Ground return and shield
34	AnalogIn	I	Analog input (range software selectable 0-5V or ±10V)

MSB AxisID register LSB

Bit 8 | Bit 7 | Bit 6 | Bit 5 | Bit 4 | Bit 3 | Bit 2 | Bit 1 | Bit 0

ID2	ID1	ID0		
Nominal[V]	Minimum[V]	Maximum[V]	IDx* Bits	IDx* Value
0.000	0.00	0.53	000	0
1.06	0.53	1.41	001	1
1.76	1.41	2.01	010	2
2.25	2.01	2.43	011	3
2.60	2.43	2.75	100	4
2.89	2.75	3.01	101	5
3.13	3.01	3.22	110	6
3.32	3.22	3.30	111	7

Remarks:

- If Bit 7 (ID2) = 1 -> TMLCAN mode is selected
- If Bit 7 (ID2) = 0 -> CANopen mode is selected
- Bit 8 (MSB of ID2) is ignored, and always considered as "0"
- The maximum AxisID value is 127 (Bit 0 ... Bit 6)
- TMLCAN mode: AxisID = (64*ID2_Value - 128) + (8*ID1_Value) + ID0_Value
- CANopen mode: AxisID = (64*ID2_Value) + (8*ID1_Value) + ID0_Value
- If all "Idx" pins are left not connected or connected to GND, the AxisID value is 255 and CANopen mode is selected. In this case, the drive will be in "LSS inactive" state and the Green LED will flash at 1 second intervals

* where "x" can be 0, 1 or 2

¹ Operating temperature at higher temperatures is possible with reduced current and power ratings

² In case of forced cooling (conduction or ventilation): a) the ambient temperature requirements may be extended substantially as long as the drive (PCB) temperature is kept below 85 °C; b) the

Pin	Name	Type	Description
1	+V USB	I	USB 5V detect input
2	GND	-	Ground return for USB
3	Hall1	I	Digital Hall, or Linear Hall sensor 1
4	Hall2	I	Digital Hall, or Linear Hall sensor 2
5	Hall3	I	Digital Hall, or Linear Hall sensor 3
6	GND	-	Ground return and shield
7	+5V	O	Supply for all feedback sensors
8	GND	-	Ground return and shield
9	EncA1+/EncA1/ Dt1+/Dt1	I	Encoder 1 A+/Data+ diff. input or single-ended input
10	EncA1-/Dt1-	I	Encoder 1 A-/Data- diff. input. Leave open for single-ended; Add externally 120Ω to pin 9 for differential
11	EncB1+/EncB1/ Clk1+/Clk1	I	Encoder 1 B+/Clock+ diff. input or single-ended input
12	EncB1/ Clk1-	I	Encoder 1 B-/Clock- diff. input. Leave open for single-ended; Add externally 120Ω to pin 11 for differential
13	EncA2+/EncA2/ Dt2+/Dt2	I	Encoder 2 A+/Data+ diff. input or single-ended input
14	EncA2-/Dt2-	I	Encoder 2 A-/Data- diff. input. Leave open for single-ended; Add externally 120Ω to pin 13 for differential
15	EncB2+/EncB2/ Clk2+/Clk2	I/O	Encoder 2 B+/Clock+ diff. input or single-ended input
16	EncB2-/ Clk2-	I	Encoder 2 B-/Clock- diff. input. Leave open for single-ended; Add externally 120Ω to pin 15 for differential
17	Z1+	I	Encoder 1 Z+ diff. input or single-ended input
18	Z1-	I	Encoder 1 Z- diff. input. Leave open for single-ended; Add externally 120Ω to pin 17 for differential
19	USB DM	I/O	USB data-
20	USB DP	I/O	USB data+

Pin	Name	Type	Description
1, 2	Rsvd.	-	Reserved. Do not connect.
3	TML RDY	O	Lit after power-on when the drive initialization ends. Turned off when an error occurs. Active high, LV-TTL.
4	TML ERR	O	Turned on when the drive detects an error condition. Active high, LV-TTL.
5, 6	Rsvd.	-	Reserved. Do not connect.

No.	Name	Color	Description		
LED1	TML ERR	RED	Turned on when the drive detects an error condition.		
LED3	TML RDY	GREEN	Lit after power-on when the drive initialization ends. Turned off when an error occurs.		

Electrical characteristics

All parameters measured under the following conditions (unless otherwise specified):

- V_{LOG} = 24 VDC; V_{MOT} = 48 VDC; F_{PWM} = 20 kHz
- Ambient temperature = 25°C (typical values) / 0°C...40°C (min/max values)
- Supplies start-up / shutdown sequence: -any-
- Load current = nominal

Operating Conditions	Min.	Typ.	Max.	Units
Ambient temperature	0		40 ^{1, 2}	°C
Ambient humidity	Non-condensing	0	90	%Rh
Altitude / pressure ³	Altitude (vs. sea level)	-0.1	0 + 2.5	Km
	Ambient Pressure	0 ²	0.75 + 1	atm
Storage Conditions	Min	Typ	Max	Units
Ambient temperature	-40		100	°C
Ambient humidity	Non-condensing	0	100	%Rh
Ambient Pressure	0		10.0	atm
ESD capability (Human body model)	Not powered; applies to any accessible part		±0.5	kV
	Original packaging		±15	kV
Mechanical Mounting	Min	Typ	Max	Units
Airflow	natural convection ² , closed box			
Spacing required for horizontal mounting ²	Between adjacent drives	10		mm
	Between drives and nearby walls	10		mm
	Space needed for drive removal	20		mm
	Between drives and roof-top	30		mm
Insertion force			40	N
Extraction force	Using recommended mating connectors	8		N

spacing requirements can be dropped down to zero; c) the surface temperature will decrease accordingly

³ Micro 4804 can be operated in vacuum (no altitude restriction), but at altitudes over 2,500m, current and power rating are reduced due to thermal dissipation efficiency.

Name ALN	First edition November 8, 2023	Document template: P099.TQT.564.0001	Last edition March 12, 2025	Visa:
 TECHNOSOFT	Title of document Micro 4804 MZ-CAN PRODUCT DATA SHEET	N° document P020.002.E102.DSH.10G	Page: 2 of 5	



Micro 4804 MZ-CAN
DATASHEET
P/N: P020.002.E102

Environmental Characteristics		Min.	Typ.	Max.	Units
Size (Length x Width x Height)		38.1 x 25 x 9.6		mm	
		~1.5 x 1 x 0.4		inch	
Weight		8		g	
Cleaning agents		Dry cleaning is recommended		Only Water- or Alcohol- based	
Protection degree	According to IEC60529	IP20		-	
Power dissipation	Idle ($I_{MOT} = 0A$)	1	1.2	W	
	Full power ($I_{MOT} = \text{nominal}$)	2.0	2.4		
Power efficiency	Full power ($I_{MOT} = \text{nominal}$)	98.7		%	
Voltage efficiency	$f_{PWM} = 20\text{KHz}$	98.3			
	$f_{PWM} = 100\text{KHz}$	91.4			
Surface temperature ¹	Idle ($I_{MOT} = 0A$)	55		°C	
	Full power ($I_{MOT} = \text{nominal}$)	100			
Logic Supply Input (+V _{LOG})		Min.	Typ.	Max.	Units
Supply voltage	Nominal values	6	24	48	V _{DC}
	Absolute maximum values, drive operating but outside guaranteed parameters	4.9		60	V _{DC}
	Absolute maximum values, continuous	-0.5		63	V _{DC}
Supply current	+V _{LOG} = 12V		90	150	mA
	+V _{LOG} = 24V		60	90	
	+V _{LOG} = 48V		45	60	
Utilization category Acc. to 60947-4-1 ($I_{PEAK} \leq 1.05 * I_{NOM}$)		DC-1			
Motor Supply Input (+V _{MOT})		Min.	Typ.	Max.	Units
Supply voltage	Nominal values	7		48	V _{DC}
	Absolute maximum values, drive operating but outside guaranteed parameters	6		60	V _{DC}
	Absolute maximum values, continuous	-0.5		63	V _{DC}
Supply current	Idle		0.3		mA
	Operating	-16	±7	+16	A
Voltage measurement error			±0.15	±0.25	V
Utilization category Acc. to 60947-4-1 ($I_{PEAK} \leq 4.0 * I_{NOM}$)		DC-3			
Supply Output (+5V)		Min.	Typ.	Max.	Units
Output voltage	Current sourced = 400mA	5.05	5.2	5.25	V
Output current	Output voltage ≥ 4.85V			1,200	mA
Short-circuit to GND protection		Yes / Drive resets at event			
Over-voltage protection		NOT protected			
ESD protection Human body model		±1			kV
Motor Outputs (A/A+, B/A-, C/B+, CR/B-)		Min.	Typ.	Max.	Units
Nominal current ²	PMPSM motors sinusoidal amplitude			±6.3	A
	PMPSM motors sinusoidal RMS			4.5	A _{RMS}
	DC/BLDC/STEP motors continuous			5.5	A
Peak current	maximum 4 seconds	-16		+16	A
Short-circuit protection threshold			±25	±28	A
Short-circuit protection delay		2.6		3.5	μs
On-state voltage drop	Nominal output current; including typical mating connector contact resistance	50	70		mV
Off-state leakage current		0.3	1		mA
Current measurement	Accuracy (FS = Full Scale)	±1	±1.5		%FS
	Noise (current ≤ 2A)	±4	±6		mA
	Noise (current ≥ 2A)	±30	±50		mA
Offset drift (compensated @ AxisOn)			±0.16		mA/°C
Motor inductance (phase-to-phase)	Recommended value to avoid spurious short-circuit protection, triggered by ripple	Fast loop ³ V _{MOT}			μH
		50μs 48V	133		
Motor electrical time-constant (L/R)		100μs 48V	266		
		50μs 24V	66		
		100μs 24V	133		
		F _{PWM} = 20 kHz	330		
Hall Inputs (Hall1, Hall2, Hall3)		F _{PWM} = 40 kHz	170		μs
		F _{PWM} = 60 kHz	140		
		F _{PWM} = 80 kHz	80		
		F _{PWM} = 100 kHz	66		
Mode compliance		TTL / CMOS / Open-collector (NPN sink), or analog (linear) 0...5V			
Default state	Input floating (Wiring disconnected)	4.5	4.8	5.2	V
Input voltage	Logic "LOW"		1.5	1.7	
	Logic "HIGH"	3	2.5		
	Hysteresis		0.5		
Input current	Logic "LOW"; Pull to GND		2.4		mA
	Logic "HIGH"; Internal 2.2kΩ pull-up to +5		0		
Minimum pulse width			66		μs
ESD protection - Human body model			±15		kV

¹ In case of forced cooling (conduction or ventilation): a) the ambient temperature requirements may be extended substantially as long as the drive (PCB) temperature is kept below 85 °C; b) the spacing requirements can be dropped down to zero; c) the surface temperature will decrease accordingly

Digital Inputs (IN0, IN1, IN2/LSP, IN3/LSN, IN4, IN5/ENA)		Min.	Typ.	Max.	Units	
Mode compliance		NPN (sink)		Logic HIGH		
Default state	Input floating (wiring disconnected)			V		
Input voltage	Logic "LOW"	IN0, IN1, IN4, IN5/ENA	1.4	1.8	V	
	Logic "HIGH"	IN0, IN1, IN4, IN5/ENA	3.1	2.5		
	Hysteresis	IN0, IN1, IN4, IN5/ENA	0.9	1.1		
	Logic "LOW"	IN2/LSP, IN3/LSN		1.4		
	Logic "HIGH"	IN2/LSP, IN3/LSN	4	3.5		
	Hysteresis	IN2/LSP, IN3/LSN		0.6		
	Floating voltage (not connected)			4.7		
	Absolute maximum, continuous	IN2/LSP, IN3/LSN, IN5/ENA	-2			
	IN0, IN1, IN4	IN0, IN1, IN4	-0.5			
				V _{LOG} +0.5		
Input current	Logic "LOW"; Pulled to GND		6.5	8	mA	
	Logic "HIGH"; Pulled to +24V		0.2	0.4		
Input frequency		0		500	kHz	
Minimum pulse		1			μs	
ESD protection - Human body model		±2			kV	
Digital Outputs (OUT0, OUT1, OUT4)		Min.	Typ.	Max.	Units	
Mode compliance		NPN (sink) 24V		Resistive, Inductive		
Load type				High-Z (floating)		
Default state	Not supplied (+V _{LOG} floating)			Logic "HIGH"		
	Immediately after power-up					
Output voltage	Logic "LOW"; output current = 1.5A for OUT0/ 0.05A for OUT1, OUT4			0.4	V	
	Logic "HIGH"; output current = 0, no load	4	4.7	5.2		
	Logic "HIGH", external load to +V _{LOG}			V _{LOG}		
	Absolute maximum, continuous (free-wheeling diodes to +V _{LOG} to GND)	-0.5		V _{LOG} +0.5		
	Absolute maximum, surge (duration ≤ 1s) [†]	-1		V _{LOG} +1		
Output current	Logic "LOW", sink current, short duration, duty cycle ≤=1%	5s max	OUT1, OUT4		A	
		OUT0				
		0.5s max	OUT1, OUT4			
		OUT0				
	Logic "LOW", sink current, continuous; V _{OUT} ≤ 0.4V	OUT1, OUT4		0.05	mA	
		OUT0		1.5		
	Logic "HIGH", source current; external load to GND; V _{OUT} ≥ 2.0V			5	mA	
	Logic "HIGH", leakage current; external load to +V _{LOG} ; V _{OUT} = V _{LOG} max = 40V	V _{LOG} =24V	0.18	0.2		
		V _{LOG} =48V	0.42	0.45		
Minimum pulse width		0.5			μs	
ESD protection - Human body model		±25			kV	
Encoder Inputs (A1+, A1-, B1+, B1-, Z1+, Z1-, A2+, A2-, B2+, B2-)		Min.	Typ.	Max.	Units	
Single-ended mode compliance		Leave A1-, B1-, Z1-, A2-, B2- floating		TTL / CMOS / Open-collector (NPN sink)		
Single-ended threshold		A1+, B1+, Z1+, A2+, B2+	1.3	1.4	1.5	
Single-ended input current		Input pulled to GND against on-board 2.2 kΩ pull-up to +5V		2.4	2.7	
Differential mode compliance		For full RS422 compliance, see ¹		TIA/EIA-422-A		
Input voltage	Hysteresis		±0.03	±0.05	V	
	Differential mode		-15	+15		
	Common-mode range (A+ to GND, etc.)		-7	+12		
Input impedance, differential		Common-mode (A1+ to GND, etc.)	2.2		kΩ	
		Differential (A1+ to A1-, etc.)	4.4			
Input frequency		Differential mode	0	15	MHz	
Minimum pulse width		Differential mode	33		ns	
ESD protection		Human body model	±30		kV	

² For current values >4A_{RMS}, pins J1/2...8 may need to be soldered instead of socketed, for long-term reliability – check socket manufacturer specifications.

³ Fast loop period of 50μs is not possible with all feedback device types.

⁴ Full RS-422 compatibility, as well as noise rejection improvement requires an external 120Ω resistor connected across each signal pair (A1+/A1-, B1+/B1-, Z1+/Z1-, A2+/A2-, B2+/B2-)

Name ALN	First edition November 8, 2023	Document template: P099.TQT.564.0001	Last edition March 12, 2025	Visa:
 TECHNOSOFT	Title of document Micro 4804 MZ-CAN PRODUCT DATA SHEET	N° document P020.002.E102.DSH.10G	Page: 3 of 5	



Micro 4804 MZ-CAN
DATASHEET
P/N: P020.002.E102

Absolute encoder interface: SSI, BISS-C, EnDAT, Tamagawa, Nikon, Sanyo Denki		Min	Typ.	Max	Units	
Single-ended mode		Not recommended, reduced robustness & speed				
Differential mode compliance		For full RS422 compliance, see ¹				
Output voltage	Differential; 50Ω differential load	1.5	3.3		V	
	Common-mode, referenced to GND	1	1.7	3		
CLOCK frequency	Nikon, Sanyo Denki	2.5, 4		MHz		
	Panasonic, Tamagawa	2.5				
	All others	1, 2, 3, 4				
Output Short-circuit protection	Common-mode voltage ±15V	Yes, protected				
DATA format	Software selectable	Binary / Gray				
		Single-turn / Multi-turn				
		Counting direction				
		CRC type				
DATA resolution	Including CRC, flags, ...			64	Bits	
	If total resolution >31 bits, some bits must be ignored by software setting to achieve a max. 31 bits resolution					
Analog Input (REF/ FDBK)		Min	Typ.	Max	Units	
Input voltage	Operational range	0...5, -10...+10		V		
	Absolute maximum values, continuous	-22		+26		
	Absolute maximum, surge (duration ≤ 1s)			±38		
Input impedance	To 1.44V	20		kΩ		
Bandwidth (-3dB)	Software selectable	0	5.3		kHz	
Resolution		12		bits		
Integral linearity				±1	bits	
Offset error	Range -10V ... +10V		±3	±10	bits	
	Range 0 ... +5V		±10	±30		
Gain error	Range -10V ... +10V		±0.3	±0.5	%	
	Range 0 ... +5V		±0.5	±0.8		
ESD protection	Human body model	±1.5			kV	
RS-232		Min.	Typ.	Max.	Units	
Compliance		TIA/EIA-232-C				
Bit rate	Software selectable	9600	115200		Baud	
Output voltage		±5	±5.7		V	
Short-circuit	232TX to GND	Guaranteed				
Input voltage	Absolute maximum, continuous	-30	+30		V	
ESD protection	Human body model	±15			kV	

CAN-Bus		Min.	Typ.	Max.	Units
Compliance		CAN 2.0B, ISO 11898-2			
Software protocols compatibility		CiA301, CiA305, CiA402, TechnoCAN, TMLcan			
Bit rate	Software selectable	125, 250, 500, 1000		Kbaud	
Node addressing	TMLcan CANopen	1 ÷ 255		-	
Voltage	Common-mode, operating	-12		+12	V
	Common-mode, max. continuous	-58		+58	V
	Differential, max. continuous	-45		+45	V
Input impedance	Differential	40		90	kΩ
	Common-mode	20		45	kΩ
Termination resistor (120Ω)		NOT included			
ESD protection	Human body model	±10			kV
AxisID inputs		Min.	Typ.	Max.	Units
Default state	ID1, ID1, ID2 floating	Configured Station Alias = 0, AxisID=255			
Internal pull-down to GND		95	100	105	kΩ
ESD protection	Human body model	±250		V	
LED outputs		Min.	Typ.	Max.	Units
Polarity	Active high (high=LED lit)				
	Common cathode to GND				
Voltage	I _{OH} ≤ 0.9mA	2.9	3.3		V
	I _{OL} ≤ 1.5mA	2.4			V
	I _{OL} ≤ 2.0mA		0	0.4	V
Current	Sink (I _{OL}) current larger than source (I _{OH}) current	-2.0		+1.5	mA
Short-circuit protection		NOT protected			
ESD protection	Human body model	±250		V	
BFS input		Min.	Typ.	Max.	Units
Polarity	Active Low (0=fail-safe boot, 1=normal)				
	High				
Voltage	BFS floating	Logic low (active)			
	Logic high (inactive)	2.0	3.3		V
	Abs. max., continuous	-0.5		3.8	V
Current	Logic low (2.2kΩ pull to +3.3V)		1.5	1.6	mA
	Logic high		0		mA
ESD protection	Human body model	±250			V


[†] Stresses beyond values listed under "absolute maximum ratings" may cause permanent damage to the device. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

¹ Full RS-422 compatibility, as well as noise rejection improvement requires an external 120Ω resistor connected across each signal pair (A1+/A1-, B1+/B1-, Z1+/Z1-, A2+/A2-, B2+/B2-)


Name ALN	First edition November 8, 2023	Document template: P099.TQT.564.0001	Last edition March 12, 2025	Visa:
 TECHNOSOFT	Title of document Micro 4804 MZ-CAN PRODUCT DATA SHEET	N° document P020.002.E102.DSH.10G		Page: 4 of 5




Micro 4804 MZ




Micro 4804 MZ




Micro 4804 MZ



Micro 4804 MZ



Micro 4804 MZ



Name ALN	First edition November 8, 2023	Document template: P099.TQT.564.0001	Last edition March 12, 2025	Visa:
TECHNOSOFT	Title of document	Micro 4804 MZ-CAN PRODUCT DATA SHEET	N° document P020.002.E102.DSH.10G	Page: 5 of 5